

NTC Thermistors, Long Immersion Sensor with Connector



DESCRIPTION

Thermistor NTC sensor, with a negative temperature coefficient, measured in accordance with IEC 60539.

QUICK REFERENCE DATA

PARAMETER	VALUE
Resistance value at 25 °C (for information)	11 979 Ω
Resistance at 80 °C	1704 Ω
Tolerance on R_{80} - value	$\pm 2 \%$
$B_{25/85}$ - value	3740K
Tolerance on $B_{25/85}$ - value	$\pm 0.75 \%$
Thermal time constant τ 63.2 % (25 °C to oil 85 °C)	15 s
Operating temperature range at zero power	- 25 °C to + 125 °C
Min. dielectric withstanding voltage between the metallic housing and the terminals/NTC	500 V _{AC}
Max. Power	150 mW
R/T values	Refer to table
Climatic category (IEC 60539)	25/125/56
Weight	19 g

FEATURES

- Rugged construction
- Temperature measurement accuracy better than $\pm 1 \text{ }^{\circ}\text{C}$ between 50 °C and 100 °C
- Stainless steel housing
- Housing is 100 % watertight
- High number of thermal cycles resistant (minimum 100 000 cycles)
- Withstanding voltage 500 V (between outer case and terminals/NTC)
- Male terminals 6.3 x 0.8. type IDC rast 5 mm, or solderless terminals FASTON (IEC 760 flat quick connections)
- Compliant to RoHS directive 2002/95/EC
- PVC-free



RoHS
COMPLIANT

APPLICATIONS

Sensor used for temperature measurement, sensing and control in:

- Water boilers
- Heating system
- Water and used water systems
- Water and oil tanks
- Consumer appliances
- Industrial appliances
- Solar heating systems

MOUNTING

- O-Ring
- U-Clip or spring
- Rast 5 mm 2 poles connector (refer to polarisation detail), or female FASTON for 6.3 x 0.8 terminals or equivalents

ELECTRICAL DATA AND ORDERING INFORMATION

SAP MATERIAL NO.	12NC	R_{25} - VALUE (k Ω)	$B_{25/85}$ - VALUE (K)	SPQ (Pieces)
NTCAIMME3C90080	2381 645 90080	11 979	3740	100


Ordering information can be found on: www.vishay.com/doc?33036

NTCAIMME3C90080/2381 645 90080



Vishay BC Components NTC Thermistors Long Immersion
Sensor with Connector

DIMENSIONS in millimeters



1.	2.	3.	L1	L2	L3	Ø D1	Ø D2	Ø D3	Ø D4	Ø D5
Thermistor NTC position	Stainless steel housing	Connector	153.5 ± 3	118	19	5 + 0.05/- 0.02	6	8.1 ± 0.1 (O-Ring)	8 (Clip)	11 + 0.05/- 0.02

R/T TABLE


TEMP. [°C]	R_T/R_{25}	RESISTANCE [Ω]	$\Delta R/R$ [%]	α [%/K]	ΔT [K]	$R_{min.}$ [Ω]	$R_{max.}$ [Ω]
- 25	10.819	129 600	8.86	- 5.52	1.60	118 123	141 078
- 20	8.244	98 762	8.40	- 5.35	1.57	90 465	107 058
- 15	6.335	75 887	7.96	- 5.19	1.53	69 844	81 930
- 10	4.907	58 777	7.54	- 5.03	1.50	54 344	63 210
- 5	3.829	45 874	7.14	- 4.88	1.46	42 600	49 147
0	3.011	36 067	6.75	- 4.74	1.42	33 634	38 500
5	2.384	28 557	6.37	- 4.60	1.38	26 738	30 376
10	1.900	22 765	6.01	- 4.47	1.34	21 398	24 132
15	1.525	18 266	5.66	- 4.34	1.30	17 233	19 299
20	1.231	14 748	5.32	- 4.22	1.26	13 964	15 532
25	1.000	11 979	4.99	- 4.10	1.22	11 382	12 577
30	0.8170	9787	4.67	- 3.99	1.17	9329	10 244
35	0.6712	8040	4.37	- 3.88	1.13	7689	8391
40	0.5543	6640	4.07	- 3.77	1.08	6370	6911
45	0.4602	5513	3.78	- 3.67	1.03	5304	5721
50	0.3839	4599	3.50	- 3.58	0.98	4438	4760
55	0.3218	3855	3.23	- 3.48	0.93	3731	3980
60	0.2710	3247	2.97	- 3.39	0.88	3150	3343
65	0.2293	2746	2.72	- 3.30	0.82	2672	2821
70	0.1947	2333	2.47	- 3.22	0.77	2275	2391
75	0.1661	1990	2.23	- 3.14	0.71	1945	2034
80	0.1422	1704	2.00	- 3.06	0.65	1670	1738
85	0.1223	1465	2.23	- 2.99	0.75	1432	1497
90	0.1055	1264	2.45	- 2.92	0.84	1233	1295
95	0.09135	1094	2.66	- 2.85	0.93	1065	1123
100	0.07936	950.7	2.87	- 2.78	1.03	920.7	980.7
105	0.06918	828.8	3.07	- 2.71	1.13	800.4	857.2
110	0.06050	724.8	3.27	- 2.65	1.23	698.0	751.5
115	0.05307	635.8	3.46	- 2.59	1.34	610.7	660.9
120	0.0467	559.4	3.65	- 2.53	1.44	535.9	582.9
125	0.04121	493.6	3.83	- 2.47	1.55	471.7	515.5

Notes

- Other resistance and tolerances values available
- Other connector polarisations available on request
- Available with insulated leads instead of connector
- Detail mounting drawing or 3D solid model available on request
- Available with platinum elements Pt500 or Pt1000 sensor

RELIABILITY DATA		
TEST	CONDITIONS	$\Delta R_{25}/R_{25}$ (typical)
Dry heat storage (steady state) IEC 60068-2-2	T = 125 °C t = 1000 h	< 1 %
Damp heat storage (steady state) IEC 60068-2-78	T = 85 °C (air) 85 % RH t = 56 days	< 1 %
Rapid temperature cycling (air) IEC 60068-2-14	T1 = - 40 °C T2 = 125 °C t < 15 s 10 000 cycles	< 1 %
Rapid temperature cycling (oil)	T1 = 25 °C T2 = 80 °C 100 000 cycles	< 1 %

TYPICAL THERMAL CYCLING RELIABILITY





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.